


Internal Telephone/Data Communications Cable - UTP Category 3

**AS/NZS 3080
ACMA - AS/CA S008**

Cable Design



- **Multi-pair construction**
- **Conductor:** Annealed solid copper wire 0.50mm diameter (24 AWG)
- **Insulation:** Polyethylene compound in compliance with AS1049
- **Cabling element:** Twisted pair
- **Colour code:** See table 1
- **Stranding of pairs:** Bunched (5 and 10 units)
- **Wrapping:** Polyethylene terephthalate tape
- **Sheath:** PVC in compliance with AS 1049. One ripcord is provided beneath the sheath for easy removal
- **Sheath (Alternative):** LSOH in compliance with AS 1049

- Drawing not to scale -

These Internal cables have been upgraded to Category 3, 100Ω balanced, suitable for Local Area Network (LAN) network cabling (Up to 16 MHz). Data-grade UTP, capable of supporting transmission rates of up to 16Mbps

Technical data

Number of Pairs		6	10	25	50	100
Cable nominal diameter	mm	6.8	8.4	11.5	15.8	21.3
Cable nominal weight	kg/km	52	75	152	280	537
Max. installation tension	kN	230	380	950	1900	3800
Min. bending radius	mm	10 x Cable OD				
Temperature range	°C	Installation 0 -> +50			Operation 0 -> +60	


Identification

Sheath Colour:

The standard outer sheath colour is manilla (off-white). The colour for the LSOH option is black.

Sheath Marking:

The outer sheath is marked in 1 meter intervals as follows:

PRYSMIAN DW M@XTEL CAT3 XXXPR INTERNAL TELEPHONE 0.50MM Part No  N10514 T/N #### MM/YY MADE IN AUSTRALIA *****

Attenuation and Near End Crosstalk (NEXT):			Electrical characteristics	
Frequency [MHz]	Max. Attenuation [dB/100m]	Min. Pr-Pr NEXT [dB/100m]	DC resistance [Ω /100m]: 9.38 Max.	
0.256	1.3	N/A	Resistance unbalance [%]: 5.0 Max.	
0.512	1.8	N/A	Characteristic impedance [Ω]: 100 \pm 15	
0.772	2.2	43.0	@1.0–16 MHz	
1.0	2.6	41.3	Capacitance unbalance [pF/100m] pair to ground	
4.0	5.6	32.3	@ 0.8 or 1.0 kHz: 330 Max.	
8.0	8.5	27.8	Note: All electrical characteristics are given at 20°C	
10.0	9.7	26.3		
16.0	13.1	23.2		

Table 1. Colour code / Pair and unit identification

Pair number	Insulation colour		Pair number	Group colour	
	Wire a	Wire b			
1	White	Blue	1 to 10	White	Blue
2	White	Orange	11 to 20	White	Orange
3	White	Green	21 to 30	White	Green
4	White	Brown	31 to 40	White	Brown
5	White	Grey	41 to 50	White	Grey
6	Red	Blue	51 to 60	Blue	Blue
7	Red	Orange	61 to 70	Orange	Orange
8	Red	Green	71 to 80	Green	Green
9	Red	Brown	81 to 90	Brown	Brown
10	Red	Grey	91 to 100	Grey	Grey

Units : 5 pairs (pairs 1 to 5); 10 pairs (pairs 1 to 10)

Logistic

Packing:

New non-returnable light weight timber drums to AS/NZS 2857 with NOLCO-FLEX protection

Delivery Lengths:

Standard delivery length is 250 or 500 m with a tolerance of - 1% / + 3%

© PrysmianGroup 2012, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by PrysmianGroup: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of PrysmianGroup. The information is believed to be correct at the time of issue. PrysmianGroup reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by PrysmianGroup.